

**SEMITOP<sup>®</sup> 2**

## IGBT Module

**SK45GB063**

**SK45GAL063**

**SK45GAR063**


Preliminary Data

### Features

- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- N channel, homogeneous Silicon structure (NPT-Non punchthrough IGBT)
- High short circuit capability
- Low tail current with low temperature dependence
- UL recognized, file no. E63532

### Typical Applications\*

- Switching (not for linear use)
- Inverter
- Switched mode power supplies
- UPS




GB

GAL

GAR

Absolute Maximum Ratings		$T_s = 25\text{ }^\circ\text{C}$ , unless otherwise specified		
Symbol	Conditions	Values		Units
<b>IGBT</b>				
$V_{CES}$	$T_j = 25\text{ }^\circ\text{C}$	600		V
$I_C$	$T_j = 125\text{ }^\circ\text{C}$	$T_s = 25\text{ }^\circ\text{C}$	45	A
		$T_s = 80\text{ }^\circ\text{C}$	30	A
$I_{CRM}$	$I_{CRM} = 2 \times I_{Cnom}$	100		A
$V_{GES}$		$\pm 20$		V
$t_{psc}$	$V_{CC} = 300\text{ V}; V_{GE} \leq 20\text{ V}; T_j = 125\text{ }^\circ\text{C}$ $V_{CES} < 600\text{ V}$	10		$\mu\text{s}$
<b>Inverse Diode</b>				
$I_F$	$T_j = 150\text{ }^\circ\text{C}$	$T_s = 25\text{ }^\circ\text{C}$	57	A
		$T_s = 80\text{ }^\circ\text{C}$	38	A
$I_{FRM}$				A
$I_{FSM}$	$t_p = 10\text{ ms}$ ; half sine wave $T_j = 150\text{ }^\circ\text{C}$	440		A
<b>Freewheeling Diode</b>				
$I_F$	$T_j = 150\text{ }^\circ\text{C}$	$T_s = 25\text{ }^\circ\text{C}$	57	A
		$T_s = 80\text{ }^\circ\text{C}$	38	A
$I_{FRM}$				A
$I_{FSM}$	$t_p = 15\text{ ms}$ ; $T_j = \text{ }^\circ\text{C}$	440		A
<b>Module</b>				
$I_{t(RMS)}$				A
$T_{vj}$		-40 ... +150		$^\circ\text{C}$
$T_{stg}$		-40 ... +125		$^\circ\text{C}$
$V_{isol}$	AC, 1 min.	2500		V

Characteristics		$T_s = 25\text{ }^\circ\text{C}$ , unless otherwise specified				
Symbol	Conditions	min.	typ.	max.	Units	
<b>IGBT</b>						
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 1\text{ mA}$	4,5	5,5	6,5	V	
$I_{CES}$	$V_{GE} = 0\text{ V}, V_{CE} = V_{CES}$	$T_j = 25\text{ }^\circ\text{C}$			0,15	mA
		$T_j = 125\text{ }^\circ\text{C}$				mA
$I_{GES}$	$V_{CE} = 0\text{ V}, V_{GE} = 30\text{ V}$	$T_j = 25\text{ }^\circ\text{C}$			120	nA
		$T_j = 125\text{ }^\circ\text{C}$				nA
$V_{CE0}$		$T_j = 25\text{ }^\circ\text{C}$			1	V
		$T_j = 125\text{ }^\circ\text{C}$			1,1	V
$r_{CE}$	$V_{GE} = 15\text{ V}$	$T_j = 25\text{ }^\circ\text{C}$			20	$\text{m}\Omega$
		$T_j = 125\text{ }^\circ\text{C}$				$\text{m}\Omega$
$V_{CE(sat)}$	$I_{Cnom} = 50\text{ A}, V_{GE} = 15\text{ V}$	$T_j = 25\text{ }^\circ\text{C}_{chiplev.}$	2,1	2,5	V	
		$T_j = 125\text{ }^\circ\text{C}_{chiplev.}$			V	
$C_{ies}$	$V_{CE} = 25, V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$			2,2	nF
$C_{oes}$						nF
$C_{res}$					0,2	nF
$Q_G$	$V_{GE} = 0 \dots 20\text{ V}$			155	nC	
$t_{d(on)}$	$R_{Gon} = 22\text{ }\Omega$	$V_{CC} = 300\text{ V}$ $I_C = 30\text{ A}$			45	ns
			$T_j = 125\text{ }^\circ\text{C}$			35
$t_r$	$R_{Goff} = 22\text{ }\Omega$	$T_j = 125\text{ }^\circ\text{C}$			1,4	mJ
$E_{on}$					250	ns
$t_{d(off)}$		$V_{GE} = \pm 15\text{ V}$			25	ns
			$T_j = 125\text{ }^\circ\text{C}$			1,2
$E_{off}$						
$R_{th(j-s)}$	per IGBT			1	K/W	



**SEMITOP® 2**

## IGBT Module

**SK45GB063**

**SK45GAL063**

**SK45GAR063**


Preliminary Data

### Features

- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- N channel, homogeneous Silicon structure (NPT-Non punchthrough IGBT)
- High short circuit capability
- Low tail current with low temperature dependence
- UL recognized, file no. E63532

### Typical Applications\*





- Switching (not for linear use)
- Inverter
- Switched mode power supplies
- UPS







Characteristics					
Symbol	Conditions	min.	typ.	max.	Units
<b>Inverse Diode</b>					
$V_F = V_{EC}$	$I_{Fnom} = 30 \text{ A}; V_{GE} = 0 \text{ V}$				
			$T_j = 25 \text{ }^\circ\text{C}_{\text{chiplev.}}$	1,45	1,7
			$T_j = 125 \text{ }^\circ\text{C}_{\text{chiplev.}}$	1,4	1,75
$V_{F0}$			$T_j = 125 \text{ }^\circ\text{C}$	0,85	0,9
$r_F$			$T_j = 125 \text{ }^\circ\text{C}$	9	16
$I_{RRM}$	$I_F = 30 \text{ A}$		$T_j = 125 \text{ }^\circ\text{C}$	16	A
$Q_{rr}$	$di/dt = -500 \text{ A}/\mu\text{s}$			2	$\mu\text{C}$
$E_{rr}$	$V_{CC} = 300 \text{ V}$			0,25	mJ
$R_{th(j-s)D}$	per diode			1,2	K/W
<b>Freewheeling Diode</b>					
$V_F = V_{EC}$	$I_{Fnom} = 30 \text{ A}; V_{GE} = 0 \text{ V}$				
			$T_j = 25 \text{ }^\circ\text{C}_{\text{chiplev.}}$	1,45	1,7
			$T_j = 125 \text{ }^\circ\text{C}_{\text{chiplev.}}$	1,4	1,75
$V_{F0}$			$T_j = 125 \text{ }^\circ\text{C}$	0,85	0,9
$r_F$			$T_j = 125 \text{ }^\circ\text{C}$	9	16
$I_{RRM}$	$I_F = 30 \text{ A}$		$T_j = 125 \text{ }^\circ\text{C}$	16	A
$Q_{rr}$	$di/dt = -500 \text{ A}/\mu\text{s}$			2	$\mu\text{C}$
$E_{rr}$	$V_{CC} = 300 \text{ V}$			0,25	mJ
$R_{th(j-s)FD}$	per diode			1,2	K/W
$M_s$	to heat sink			2	Nm
w				19	g

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

\* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.







Case T4 (Suggested hole diameter, in the PCB, for solder pins and plastic mounting pins: 2mm)

