

**SEMITOP<sup>®</sup> 2**

## IGBT Module

**SK8GD126**


Preliminary Data

### Features

- Fast TRENCH IGBTs
- Soft freewheeling diodes in CAL High Density technology
- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)

### Typical Applications\*


- Switching (not for linear use)
- Inverter
- Switched mode power supplies
- UPS



GD

Absolute Maximum Ratings		$T_s = 25\text{ °C}$ , unless otherwise specified		
Symbol	Conditions	Values		Units
<b>IGBT</b>				
$V_{CES}$	$T_j = 25\text{ °C}$	1200		V
$I_C$	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	15	A
		$T_s = 80\text{ °C}$	10	A
$I_{CRM}$	$I_{CRM} = 2 \times I_{Cnom}$	16		A
$V_{GES}$		$\pm 20$		V
$t_{psc}$	$V_{CC} = 600\text{ V}; V_{GE} \leq 20\text{ V}; T_j = 125\text{ °C}$ $V_{CES} < 1200\text{ V}$	10		$\mu\text{s}$
<b>Inverse Diode</b>				
$I_F$	$T_j = 150\text{ °C}$	$T_s = 25\text{ °C}$	13	A
		$T_s = 80\text{ °C}$	9	A
$I_{FRM}$	$I_{FRM} = 2 \times I_{Fnom}$			A
$I_{FSM}$	$t_p = 10\text{ ms}; \text{half sine wave } T_j = 150\text{ °C}$	55		A
<b>Module</b>				
$I_{t(RMS)}$				A
$T_{vj}$		-40 ... +150		$^{\circ}\text{C}$
$T_{stg}$		-40 ... +125		$^{\circ}\text{C}$
$V_{isol}$	AC, 1 min.	2500		V

Characteristics		$T_s = 25\text{ °C}$ , unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
<b>IGBT</b>					
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 0,3\text{ mA}$	5	5,8	6,5	V
$I_{CES}$	$V_{GE} = 1200\text{ V}, V_{CE} = V_{CES}$	$T_j = 25\text{ °C}$	0,05		mA
		$T_j = 125\text{ °C}$			mA
$I_{GES}$	$V_{CE} = 0\text{ V}, V_{GE} = 20\text{ V}$	$T_j = 25\text{ °C}$	120		nA
		$T_j = 125\text{ °C}$			nA
$V_{CE0}$		$T_j = 25\text{ °C}$	1	1,2	V
		$T_j = 125\text{ °C}$	0,9		V
$r_{CE}$	$V_{GE} = 15\text{ V}$	$T_j = 25\text{ °C}$	87,5		$\text{m}\Omega$
		$T_j = 125\text{ °C}$	137		$\text{m}\Omega$
$V_{CE(sat)}$	$I_{Cnom} = 8\text{ A}, V_{GE} = 15\text{ V}$	$T_j = 25\text{ °C}_{chiplev.}$	1,7	2,2	V
		$T_j = 125\text{ °C}_{chiplev.}$	2		V
$C_{ies}$	$V_{CE} = 25, V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$	0,605		nF
$C_{oes}$			0,037		nF
$C_{res}$			0,029		nF
$t_{d(on)}$	$R_{Gon} = 50\ \Omega$	$V_{CC} = 600\text{ V}$ $I_C = 8\text{ A}$	85		ns
$t_r$			30		ns
$E_{on}$	$R_{Goff} = 50\ \Omega$	$T_j = 125\text{ °C}$ $V_{GE} = \pm 15\text{ V}$	0,78		mJ
$t_{d(off)}$			430		ns
$t_f$			90		ns
$E_{off}$			0,96		mJ
$R_{th(j-s)}$	per IGBT			2	K/W



**SEMITOP® 2**

## IGBT Module

**SK8GD126**


Preliminary Data

### Features

- Fast TRENCH IGBTs
- Soft freewheeling diodes in CAL High Density technology
- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)

### Typical Applications\*

- Switching (not for linear use)
- Inverter
- Switched mode power supplies
- UPS







GD




### Characteristics


Symbol	Conditions	min.	typ.	max.	Units
<b>Inverse Diode</b>					
$V_F = V_{EC}$	$I_{Fnom} = 8 \text{ A}; V_{GE} = 0 \text{ V}$				
			1,9	22	V
			2	2,4	V
$V_{F0}$			1	1,1	V
			0,8		V
$r_F$			112	138	mΩ
			150		mΩ
$I_{RRM}$	$I_F = 8 \text{ A}$		9,4		A
$Q_{rr}$	$di/dt = -300 \text{ A}/\mu\text{s}$		1,5		μC
$E_{rr}$	$V_{CC} = 600\text{V}$		20,6		mJ
$R_{th(j-s)D}$	per diode			2,8	K/W
$M_s$	to heat sink			2	Nm
w			21		g

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.


\* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.







Case T47 (Suggested hole diameter, in the PCB, for solder pins and plastic mounting pins: 2mm)



Case T47

GD